



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>A61K 7/155</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 98/44898</b> <b>(43) International Publication Date:</b> 15 October 1998 (15.10.98)
<p><b>(21) International Application Number:</b> PCT/GB98/00950</p> <p><b>(22) International Filing Date:</b> 30 March 1998 (30.03.98)</p> <p><b>(30) Priority Data:</b>          97400811.2                      9 April 1997 (09.04.97)                      EP  <i>(34) Countries for which the regional or international application was filed:</i>                      FR et al.          9711447.4                      4 June 1997 (04.06.97)                      GB</p> <p><b>(71) Applicant (for all designated States except MN US):</b> RECKITT &amp; COLMAN FRANCE [FR/FR]; 15, rue Ampère, Boîte Postale 83, F-91301 Massy Cedex (FR).</p> <p><b>(71) Applicant (for MN only):</b> RECKITT &amp; COLMAN PRODUCTS LIMITED [GB/GB]; One Burlington Lane, London W4 2RW (GB).</p> <p><b>(72) Inventors; and</b>  <b>(75) Inventors/Applicants (for US only):</b> GUILLAUME, Bruno [FR/FR]; 3, impasse de la Chesnaye, Craches, F-78660 Prunay en Yvelines (FR). LEDON, Philippe [FR/FR]; 5, hauts de Chateau, F-28300 Saint Prest (FR). CANELAS, Annick [FR/FR]; 53, rue de Voves, F-28630 Le Coudray (FR). ACHER, David [FR/FR]; 1, rue Jean Laillet, Appartement 10, F-28000 Chartres (FR). HEMERY, Séverine</p>		<p>[FR/FR]; Les Oeillets 16, La Potinière, F-27320 Nonancourt (FR). DAHMS, Gerd [DE/DE]; Beerenbusch 11, D-42549 Velbert (DE). DESMOTS, Sarah [FR/FR]; 4, rue de la Fulda, F-28100 Dreux (FR). DELAGNEAU, Hubert [FR/FR]; 14, rue des Tilleuls, Bailleau l'Eveque, F-28300 Mainvilliers (FR).</p> <p><b>(74) Agents:</b> ILOTT, Elizabeth, Anne et al.; Reckitt &amp; Colman plc, Group Patents Dept., Dansom Lane, Hull HU8 7DS (GB).</p> <p><b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b>  <i>With international search report.</i></p>
<b>(54) Title:</b> DEPILATORY COMPOSITIONS, THEIR PREPARATION AND USE		
<p><b>(57) Abstract</b></p> <p>A depilatory composition in the form of an aqueous gel comprises a substance capable of degrading hair keratin and a water-soluble polymeric binder and is buffered to a pH of from 10.5 to 13.0. The polymeric binder is formed from a first component that is a charged cross-linked polymer and a second component that comprises a linear non-ionic and/or charged polymer. The composition is preferably in the form of a stable gel that can be applied by means of a pump spray.</p>		

***FOR THE PURPOSES OF INFORMATION ONLY***

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**DEPILATORY COMPOSITIONS, THEIR PREPARATION AND USE**

This invention relates to depilatory compositions, in particular those in the form of a gel.

5

Compositions for removing superfluous body hair are well known. These are of various types. One type of composition is in the form of a cream containing a depilatory agent which degrades hair keratin. In the case of a depilatory cream, hair is removed by applying the cream to an area of skin to be depilated, leaving the cream on the skin for sufficient time for the hair to be chemically dissolved, and then wiping and/or washing the cream and unwanted hair from the skin. Another type of composition is in the form of a wax, which is initially heated before being applied to the skin in a generally molten state. It is then allowed to solidify before being removed from the skin together with unwanted hair.

10

15

20

British patent specification no. GB 2 223 170 discloses a two-part depilatory composition in which the first part comprises polyvinyl alcohol (PVA) and the second part comprises borax and a polyhydroxy alcohol, or Congo red; the second part functioning to effect a controlled rate of cross-linking of the PVA. After *in situ* cross-linking, such compositions solidify, requiring the use of a plasticiser to enable the solid to be peeled from the skin. Such compositions preferably also include a surfactant.

25

30

Depilatory compositions in the form of a gel are less common and attempts to market such gels have had

-2-

only limited success. The gels tended to have a higher skin irritancy than cream depilatories and became very sticky when being rinsed off because of the nature of the polymer present in the formulation. Moreover, depilatory compositions need to be of high  
5 pH, and problems were encountered in formulating a gel which would be stable in such highly alkaline conditions.

It is an aim of the present invention to provide a  
10 depilatory composition in the form of a gel which does not suffer from these disadvantages.

It is a further aim of the present invention to provide a depilatory composition in the form of a gel which may be sprayed onto the skin without  
15 propellant.

It is another aim of the present invention to provide a depilatory gel having a reduced tendency to irritate the skin.

20 It has been found that these aims can be achieved by forming a gel from two water-soluble polymeric components and in a pH environment maintained by a preferred buffer system. One of the polymeric components provides the gel with appropriate  
25 viscosity and the other polymeric component contributes to the stability of the gel.

Accordingly, one aspect of the present invention provides a depilatory composition in the form of an aqueous alkaline gel comprising:-  
30

-3-

- (i) a first polymeric binder comprising a charged, cross-linked, water-soluble polymer;
- 5 (ii) a second polymeric binder comprising a linear, water-soluble polymer;
- (iii) a depilatory agent; and
- 10 (iv) a buffer system capable of maintaining the pH of the composition at a value of from 10.5 to 13.0.

Preferably, the composition remains in the form of an aqueous alkaline gel in use.

- 15 According to another aspect of the present invention, there is provided a process for producing a depilatory composition, which process comprises:-

- 20 (i) forming a first premix by mixing water and a first polymeric binder comprising a charged, cross-linked, water-soluble polymer; forming a second premix by mixing water, a buffer and a second polymeric binder comprising a linear, water-soluble polymer; and optionally forming a third  
25 premix by mixing a depilatory agent and a keratin degradation accelerator;
- (ii) adding a depilatory agent or the third premix to the second premix with stirring;

30

-4-

(iii) adding the first premix to the resultant mixture with stirring; and

(iv) adjusting the pH to between 10.5 and 13.0.

5

The depilatory compositions of the present invention accordingly possess unique rheological qualities, which can be defined *inter alia* by their characteristic viscosity properties. For example, the shear rate (in seconds<sup>-1</sup>) needed to decrease the viscosity of the gel by half is in the range of from about 10<sup>-2</sup> s<sup>-1</sup> to about 200 s<sup>-1</sup>, preferably from about 1 s<sup>-1</sup> to about 50 s<sup>-1</sup>. Such a large drop in the viscosity of depilatory compositions is not seen with prior art formulations over these shear rate ranges. At a low shear rate of about 10<sup>-2</sup> s<sup>-1</sup>, the viscosity of the compositions of the present invention is of the order of 10<sup>3</sup> Pas (10<sup>6</sup> cP), whereas at a high shear rate of about 500 s<sup>-1</sup>, their viscosity is of the order of about 0.1 Pas (100 cP). At a very high shear rate of the order of 4x10<sup>4</sup> s<sup>-1</sup>, such as that effected by a spray-pump (see Table 2 below), it is extremely difficult to measure viscosity, but it can be envisaged that that of the compositions of the present invention would be very low.

Preferably, a gel in accordance with the present invention has unique viscosity and elasticity, sustained high ionic strength and high pH.

The cross-linked polymer of the first component is such that it swells at high pH (pH 10.5 to 13) and preferably has only carbon-carbon bond

-5-

cross-linkages. More preferably, the elastic modulus of the first component is in the range of from 200 Pa to 1000 Pa, conveniently, 400 Pa to 600 Pa, when measured at a frequency of 10 rad/s; at a temperature of 20°C and a strain of 0.1. The elastic (storage) modulus ( $G'$ ) corresponds to the energy which can be stored and released by the material.

Suitable first components include a cross-linked acrylic polymer such as a carbomer, for example, Ultrez 10 and/or Carbopol ETD 2020 from Goodrich, and Structure 2000 and 3001 from National Starch. Another suitable polymer is a cross-linked polyacrylamide such as Seppigel 305. Most preferably, the polymer of the first component is a copolymer of methyl vinyl ether and maleic anhydride cross-linked with dodecadiene available from ISP under the trade designation Antaron Stabilise 06.

Preferably, the depilatory composition includes from 0.1% to 3.0% by weight of the first component.

The second component is a linear non-ionic polymer and/or a positively charged polymer and/or a negatively charged polymer. The second, linear component is one which acts as a suspending agent for the gel and moderates the elastic modulus thereof to enable spreadability. Any suitable linear polymer may be chosen which enables the gel structure to be maintained at the osmotic pressure in the composition. Such linear polymers include hydrophilic polymers having a molecular weight of less than about 600 and non-ionic gel-forming polymers. For example, the second component may

-6-

comprise a water-soluble non-ionic polymer such as polyethylenimine, polyethylene oxide or polyethylene glycol (PEG), a hydrophobically-modified polyol such as Acrysol 44 from Rohm and Haas, or a polyvinyl pyrrolidone such as PVP K from ISP or Luviskol from BASF.

Alternatively, or additionally, the second component may comprise a natural water-soluble polymer such as cellulose, hydroxypropyl cellulose, cetyl hydroxyethyl or propyl cellulose (for example Natrosol Plus from Aqualon), starch, polyglucoside, a polysaccharide such as an alginate, guar gum, carrageenan (lambda, kappa, iota), a sclerotium gum, a polypeptide with or without any alkyl chain (C1 to C18) modification and cationic end groups such as quaternary ammonium groups with counter ions such as chlorides and bromides, or a copolymer of sodium acrylate and dimethyl diallyl ammonium chloride (such as that known as Merquat), or a copolymer of hydroxy ethyl cellulose and dimethyl diallyl ammonium chloride (such as that known as Celquat).

Most preferably, the second component comprises polyethylenimine (such as that known under the trade name Lupasol from BASF) and/or polyvinyl pyrrolidone (such as that known under the trade designation PVP K-30 from ISP).

Preferably, the depilatory composition includes from 0.2% to 3.0% by weight of the second component.

The first and second components, when combined in accordance with the present invention, form a

-7-

polymeric binder having unique viscosity and elasticity.

5 The depilatory agent may comprise any substance capable of degrading keratin and may be, for example, a sulphur compound such as potassium thioglycolate, dipotassium thioglycolate or thioglycerol.

10 Preferably, the depilatory composition includes from 0.1% to 6.0% by weight of depilatory agent, preferably from about 3.0% to 5.0%.

15 Also, the composition may optionally include component(s) which will accelerate the keratin reduction reaction such as urea, thiourea or dithioerythritol, dimethyl isosorbide (DMI), ethoxydiglycol (Transcutol) and methyl propyldiol (MP diol). DMI is preferred.

20 It is important that the pH of the composition is in the range of from about 10.5 to 13, and preferably about 11.0 to 12.5, to provide good depilation within about 5 minutes. In order to achieve this, a suitable buffer should be present, such as sodium silicate and/or L-arginine, sodium nicotinate and potassium polyethylenimine or a phosphate.

25 Generally, the buffer system will be present in an amount of from about 2.0% to 8.0% by weight, preferably from about 2.0% to 4.0% by weight.

30 Advantageously, the buffer system comprises from 2.0% to 3.0% by weight of L-arginine and from 0 to 1.0% by weight of polyethylenimine.

-8-

The pH buffer system preferably ensures efficacy of the depilation within 5 minutes whilst also minimizing skin irritation.

5

In order to achieve minimum skin irritation, a composition including L-arginine and/or polyethylenimine, urea and potassium and/or dipotassium thioglycolate is preferred.

10

In accordance with a preferred depilatory composition of the present invention, there is provided an aqueous alkaline gel comprising:

15

(i) 0.1% to 3.0% w/w of a first polymeric binder comprising a charged, cross-linked, water-soluble polymer, preferably a copolymer of methyl vinyl ether and maleic anhydride cross-linked with dodecadiene;

20

(ii) 0.2% to 3.0% w/w of a second polymeric binder comprising a linear, water-soluble polymer, preferably polyethylenimine and/or polyvinyl pyrrolidone;

25

(iii) 0.1% to 6.0% w/w, preferably 3.0% to 5.0% w/w of a depilatory agent, preferably potassium and/or dipotassium thioglycolate;

30

(iv) 2.0% to 6.0% w/w, preferably 2.0% to 4.0% w/w of a buffer system, preferably L-arginine and/or polyethylenimine; and, optionally,

-9-

- (v) 5.0% to 10.0% w/w of an accelerator for the degradation of keratin, preferably urea;

whereby the composition preferably remains in the form of an aqueous alkaline gel in use.

5

The gels according to the present invention are preferably transparent and remain transparent in use, depending on the amount of active ingredients present and on the procedure of mixing. Generally, they have a thick, rich feel and excellent rinsability with water. Moreover it is not necessary to include a surfactant in the compositions of the present invention, and hence they are less likely to cause skin damage.

10

15

Due to the special rheology of the polymeric binder, it is possible to include beads, dyes and/or oily particles which will remain dispersed in the gel. Optional excipients include compounds for soothing the skin such as azulene or jojoba and polyethylene glycol ester to reduce irritation. Suitable beads include encapsulated algae extract and sweet almond oil (Elespher). It is also possible to include hydrating, accelerating and/or reducing agents in beads. For example, water-soluble materials such as urea, potassium thioglycolate or thioglycerol can be included in beads, so that these actives are encapsulated.

20

25

Although it is possible to provide a gel in accordance with the present invention that has visco-elastic properties suitable for spraying, the depilatory material may alternatively be applied by

30

-10-

means of a roll-on device or in conventional shower gel packaging.

5 Other ingredients may be included in the compositions of the invention, such as are known in the art.

Unless otherwise stated, all percentage weights referred to herein are % weights based on the weight of the total composition.

10

For a better understanding of the invention and to show how the same may be carried into effect, reference will now be made, by way of example, to the accompanying drawings, in which:-

15

Figure 1 is a graph of shear stress (Pa) against shear rate ( $s^{-1}$ ) for a series of polymeric binders (first component) for the composition of the invention;

20

Figure 2 is a graph of the yield points (Pa) of the binders of Figure 1 against the cross-linked polymer (first component) contents (% w/w) of the binders;

25

Figure 3 is a graph of viscosities (Pas) of the binders of Figure 1 against the shear rate ( $s^{-1}$ ) of the binders; and

Figure 4 is a graph of the elastic ( $G'$ ) and viscous ( $G''$ ) moduli against stress/strain (Pa) of the first component of the composition.

30

The following Examples illustrate the invention:

**EXAMPLES 1 TO 6**

A series of depilatory gels was prepared having the compositions shown in the following Table 1:

5

**TABLE 1**

	1	2	3	4	5	6
<b>Phase 1</b>						
Polymer A	3.0%	2.5%	2.25%	2.0%	1.5%	1.0%
10 deionised water	47.0%	39.0%	36.35%	31.4%	23.5%	15.7%
<b>Phase 2</b>						
Polymer B	2.0%	2.0%	2.0%	2.0%	2.0%	2.0%
pH buffer	3.0%	3.0%	3.0%	3.0%	3.0%	3.0%
15 deionised water	10.7%	19.2%	24.8%	26.4%	38.3%	45.8%
<b>Phase 3</b>						
20 potassium thioglycolate (30%)	14.7%	14.7%	14.7%	14.7%	14.7%	14.7%
urea	8.0%	8.0%	8.0%	8.0%	8.0%	8.0%
<b>Final mix</b>						
Phase 1	50.0%	41.5%	37.5%	33.4%	25.0%	16.7%
Phase 2	15.7%	24.2%	29.8%	33.4%	43.3%	50.8%
25 Phase 3	22.7%	22.7%	22.7%	22.7%	22.7%	22.7%
Potassium hydroxide 50%	11.6%	11.6%	10.0%	10.5%	9.0%	9.8%
<b>Total</b>	100%	100%	100%	100%	100%	100%
30 Total deionised water	57.5%	58.0%	59.9%	59.6%	1.6%	61.3%

-12-

5 All amounts are expressed as % weight/weight total composition. Polymer A was a methyl vinyl ether/maleic anhydride copolymer cross-linked with dodecadiene known under the trade designation Antaron ST06 from ISP; and polymer B was polyvinyl pyrrolidone known under the trade designation PVP K-30 from ISP. The pH buffer system was a combination of 2% w/w of L-arginine and 1% w/w of polyethylenimine.

10 In each case, an Olsa mixer with planar stirring and a high shear stirrer equipped with a vacuum and heating/cooling system was used. The procedure was as follows:

**Phase 1: Premix polymer A and water.**

15 The water was placed in the mixer and polymer A was added slowly with stirring. When the polymer had been dispersed, heating was commenced whilst maintaining a vacuum of about 0.5 to 0.8 bar to avoid air bubbles. The vacuum pump was operating  
20 intermittently in order to reduce water loss. When the temperature had reached about 80°C an almost clear gel had been formed. This was allowed to cool and swell overnight.

**Phase 2: Premix polymer B, water, pH buffer**

25 The water and polymer B were introduced into the mixer and homogenised for 2 minutes. The pH buffer system was then added and the mixture homogenised for a further 2 minutes.

30

-13-

**Phase 3: Urea and potassium thioglycolate**

The urea was added to the potassium thioglycolate in a beaker and stirred for 1 hour to complete dissolution.

5

**Final mixing:** The final mixing was effected as follows:-

Phase 2 was placed in the vessel and phase 3 was added with stirring for 15 minutes. A white precipitate appeared. Phase 1 was added while mixing slowly under vacuum (0.5 bar) with planar stirring and the high shear stirrer operated at low speed. The mixture was homogenised for 30 minutes until a lumpy gel had been formed. The potassium hydroxide was then added. The gel became clear and transparent. The pH was adjusted, as necessary, to from 11.0 to 12.5.

Each of the resultant gels was subjected to rheological measurement. The parameters considered were shear stress, shear rate, viscosity and yield point. The results are shown in the Figures.

As can be seen from Figure 1, the variation of shear stress with shear rate is non-linear between 0 and  $500 \text{ s}^{-1}$  and thus the gel has a non-Newtonian behaviour with a yield point. The yield point is the stress required to make the gel flow. Figure 2 shows that the variation of the yield point ( $\tau_0$ ), i.e. the shear stress for zero shear rate, varies exponentially. For a small variation in the amount of polymer A, the variation in the yield point, i.e. the variation in spreadability or consistency, may be significant.

-14-

The following table, Table 2, gives characteristic shear rates of products to be sprayed with a conventional pump spray and products to be applied from a shower gel packaging.

5 TABLE 2

Type of packaging	Flow Rate (from packaging) of product (cm <sup>3</sup> /s)	Radius of the external output (cm)	Shear rate (s <sup>-1</sup> )
10 Pump Spray	0.17	0.0175 (radius of the actuator)	500-40000
15 Shower gel packaging	8.8	ca 0.15	500-30000

The relationship between shear rate and viscosity is shown in Figure 3, from which it can be seen that, at the shear rates given in Table 2, the viscosity is very low.

20

It has been found that, in order for the gel to be sprayable with a pump spray, its yield point should be not more than from 100 to 200 Pa. If, however, the gel is to be used in a shower gel pack, the yield point may be as high as 300 Pa. Also, in order for  
 25 the product to remain still for 5 minutes on the skin when held vertical, the yield point needs to be about 60 Pa or more. Thus gels wherein polymer A constitutes from 2.0% to 2.5% w/w are preferred for spraying, whereas rather lower percentages of  
 30 polymer A may be present where the gel is to be used in the form of a shower gel packaging.

-15-

In a further series of experiments, the blue powder Azulene was dissolved in thick paraffin oil to produce a 1% w/w solution. 2% w/w of this solution was then slowly added to each of the above gels and stirred for 5 minutes. The Azulene remained stably suspended within the gel in the form of blue oily droplets. Depending upon the concentration of Azulene in the premix and the concentration of premix in the gel, the size and colour of the droplets and the overall transparency of the gel could be adjusted.

In a further series of experiments, 0.5% w/w of Elespher was slowly added to each gel and stirred for 5 minutes. Elespher consists of encapsulated beads of algae extract and sweet almond oil, and is green in colour. The beads were stably suspended in the gel.

**EXAMPLE 7**

Gels were made in accordance with the following Table 3:

TABLE 3

		%w/w
	<b>Phase 1</b>	
	polymer A	1-3
	water	40.0
	KOH 50%	4.0
	Total phase 1	47.0

-16-

	<b>Phase 2</b>	
	polymer B	0.6-3
	buffer system	3.0
5	water	8.2
	Total phase 2	11.8
	<b>Phase 3</b>	
	water	6.5
10	potassium thioglycolate (30%)	14.7
	Total phase 3	29.2
	water	to 100.0
	KOH 50%	6.15

15

The amount of water was varied depending upon the  
 amounts of polymers A and B present. Polymers A and  
 B were as used in Examples 1 to 6 and the mixing  
 technique employed was as described in those  
 Examples. In each case, stable, sprayable depilatory  
 20 gels were obtained. This showed that for a range of  
 polymer A between 1.0% and 3.0%, a range of polymer B  
 between 0.6% and 3.0% could be used and a stable,  
 sprayable gel formed.

25

30

**CLAIMS**

1. A depilatory composition in the form of an aqueous alkaline gel comprising:

- 5 (i) a first polymeric binder comprising a charged, cross-linked, water-soluble polymer;
- (ii) a second polymeric binder comprising a  
10 linear, water-soluble polymer;
- (iii) a depilatory agent; and
- (iv) a buffer system capable of maintaining the pH  
15 of the composition at a value of from 10.5 to 13.0.

2. A depilatory composition as claimed in claim 1, wherein the cross-linked polymer of the first component is a cross-linked acrylic polymer, a  
20 cross-linked polyacrylamide or a copolymer of methyl vinyl ether and maleic anhydride cross-linked with dodecadiene.

3. A depilatory composition as claimed in claim 1 or 2, which includes from 0.1 to 3.0% w/w of the first  
25 component.

4. A depilatory composition as claimed in any of claims 1 to 3, wherein the second component comprises a linear, non-ionic polymer and/or positively charged polymer and/or negatively charged polymer.  
30

-18-

5. A depilatory composition as claimed in claim 4, wherein the second component comprises one or more of polyethylenimine, polyvinyl pyrrolidone, polyethylene oxide, polyethylene glycol, cellulose, hydroxy propyl cellulose, cetyl hydroxy ethyl cellulose, cetyl  
5 hydroxy propyl cellulose, starch, a polyglucoside, a polysaccharide, guar gum, carrageenan, a sclerotium gum, a polypeptide, and a copolymer of sodium acrylate or of hydroxy ethyl cellulose with dimethyl diallyl ammonium chloride.
- 10 6. A depilatory composition as claimed in any preceding claim, which includes from 0.2 to 3.0% w/w of the second component.
- 15 7. A depilatory composition as claimed in any preceding claim, wherein the depilatory agent is potassium thioglycolate or thioglycerol.
- 20 8. A depilatory composition as claimed in any preceding claim, including an accelerator for the degradation of keratin, such as urea, thiourea, dithioerythritol, ethoxydiglycol or methylpropyldiol.
- 25 9. A depilatory composition as claimed in any preceding claim, including a buffer system comprising a silicate, arginine such as L-arginine, a nicotinate, polyethylenimine or a phosphate.
10. A depilatory composition as claimed in any preceding claim and having a yield point of not more than 200 Pa.

30

-19-

11. A depilatory composition as claimed in any preceding claim, wherein the shear rate needed to decrease the viscosity of the gel by half is in the range of from  $10^{-2} \text{ s}^{-1}$  to  $200 \text{ s}^{-1}$ , preferably from  $1 \text{ s}^{-1}$  to  $50 \text{ s}^{-1}$ .

5

12. A depilatory composition as claimed in any preceding claim, in the form of a sprayable gel.

13. A process for producing a depilatory composition as claimed in any preceding claim, which process comprises:-

10

(i) forming a first premix by mixing water and the first component; forming a second premix by mixing water, a buffer and the second component; and optionally forming a third premix by mixing a depilatory agent and a keratin degradation accelerator;

15

(ii) adding a depilatory agent or the third premix to the second premix with stirring;

20

(iii) adding the first premix to the resultant mixture with stirring; and

(iv) adjusting the pH to between 10.5 to 13.0.

25

30

Fig.1.




Fig.2.






Fig.3.





# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 98/00950

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 A61K7/155

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 91 02538 A (JOHN MORRIS CO., INC.) 7 March 1991 see example 9	1
A	EP 0 196 896 A (NITTO ELECTRIC IND. CO., LTD) 8 October 1986	1
A	US 4 842 610 A (H. GORDON ET AL.) 27 June 1989	1
A	DATABASE "CHEMICAL ABSTRACTS" (HOST: STN), Abs.110: 198 956, Columbus, OH, USA; & JP 63 313 618 (OSAKA AEROSOL IND. CO.) 21 December 1988 XP002071920	1
A,P	FR 2 751 873 A (C. DES GARETS) 6 February 1998	1



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

**Special categories of cited documents:**

"A" document defining the general state of the art which is not considered to be of particular relevance  
"E" earlier document but published on or after the international filing date  
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)  
"O" document referring to an oral disclosure, use, exhibition or other means  
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention  
"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone  
"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.  
"&" document member of the same patent family

Date of the actual completion of the international search

17 July 1998

Date of mailing of the international search report

29/07/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Glikman, J-F

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 98/00950

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9102538 A	07-03-1991	AU 6425590 A CA 2065044 A EP 0487648 A JP 5503071 T	03-04-1991 19-02-1991 03-06-1992 27-05-1993
EP 196896 A	08-10-1986	JP 62192316 A JP 61220612 A JP 1794446 C JP 4080682 B JP 61276506 A US 4830633 A	22-08-1987 30-09-1986 14-10-1993 21-12-1992 06-12-1986 16-05-1989
US 4842610 A	27-06-1989	NONE	
FR 2751873 A	06-02-1998	NONE	